FLOOR ACCESS

HIAC RECESSED FLOOR ACCESS

HIAC RECESSED ACCESS COVERS HIAC

Surespan HIAC recessed access hatches have a pan type door and can be recessed from 3mm to 100mm. The hatches are rated from FACTA class A-E. The hatches are manufactured from aluminium or stainless steel and operated by either stainless steel gas springs, 24v DC actuators or hydraulics.

This access hatch type is not watertight, if a self draining cover is required please specify. Any water passing the seals will be dispersed via an integral drainage channel, which is fitted with an optional internal or external $\frac{3}{4}$ inch flexible hose adaptor (for connection to drain by others).

As part of the initial enquiry the weight of the infill must be advised to enable us to determine the method of operation.

HIAC ACCESS COVER - SINGLE LEAF

HIAC ACCESS COVER - DOUBLE LEAF

OPTIONAL FEATURES

- Retractable safety grid
- Retractable hand hold
- Retractable single pole
- Retractable protection covers
- Drainage connection
- Powder coated (RAL colours)
- SUREGRIP® Non slip coating
- Viewing window
- Electric
- Hydraulic (for larger hatches)
- Stainless steel
- Stainless steel trim
- Loading
- Acoustic to Rw45dB
- Fire rating
- Internal pull handle
- SureGuard handrail

LOCKING OPTIONS

OPTION CODE SG RH RP RPC DC PC/RAL (Underside only) **SGRIP** vw E HYD SS304 or SS316 SST A-F 45Db FR60, FR120, FR180 **IPH SURG**

CUSTOM MADE TO ANY SIZE



den 7 1.sal 🔶 DK-2620 Albertslund 🔶 Denmark 🔶 +45 6080 2973 🔶 www.loftlvs.dk 🔶 email: info@loftlvs.