

**Bullet IP66**

**Bullet**


Surface mounted Exterior Flood Light for ground or wall mounted application

**Features**

- Die-cast and extrusion aluminium housing with tempered glass, silicone gaskets, and stainless steel hardware.
- Polyester powder paint resistant to outdoor atmospheric conditions.
- Specular or anodized aluminium reflector.
- Base diameter 110mm with single cable entry Base diameter 150mm with double entry for through wiring.
- Electronic transformer or control gear integral incorporated inside the base.
- Designed and manufactured to comply with European standard EN 60596.

**Applications**

- Ideal for lighting to emphasize architecture details.
- Application areas: facades, lighting sculptures, architectural enhancement, highlighting plants, trees and signage.



**Bullet LED RGB**

**3180** With 12x1Wmax RGB-DMX

Inclusive of remote Control Unit with 220-240V 50/60Hz Electronic power supply and DMX signal converter with Male/Female In-Out cables for multiple connections. (Occupies 3 control channels.)

With a DMX switchboard that you can purchase separately from the market (or order our Art. 2975) you can control many more fittings, completely controlling scenes, speeds and color sequences.

IP66

**Bullet LED WHITE**


**3181** With 12W (12x1W) LED WHITE

Inclusive of Integral driver 220-240V 50/60Hz.

White Leds colours in code 93(warm 3300K) or 95(cool 6800K), other colours on request. White Leds optics in code F(Flood) or NB(Narrow Beam), other optics on request.

Dimmable version is available upon request.

IP66



**Bullet**

**3027** 100W E27 PAR 30 Halogen

**3029** Spot Light 10°

**3071** Flood Light 40°

70W G12 CDM-T Metal halide

IP66


**3185** Spot Light 10°

**3186** Flood Light 40°

150W G12 CDM-T Metal halide


With Integral Electronic ballast.

IP66




For 150W only

Art. 3027, 3029, 3071



Art. 3185, 3186



**Bullet with Extended Arm**

**3182** 100W E27 PAR 30 Halogen

**3183** Spot Light 10°

**3184** Flood Light 40°

70W G12 CDM-T Metal halide

**3305** Spot Light 10°


**3306** Flood Light 40°

150W G12 CDM-T Metal halide



With Integral Electronic ballast.

IP66

Art. 3182, 3183, 3184



Art. 3305, 3306



10

29



### Mini-Bullet



**3023** 50W 230/12V GU5.3 MR16

With Integral Electronic transformer.

IP66

**3022** 50W 230V E27 PAR20 Halogen

IP66



### Mini-Bullet

**3025** 35W E27 PAR20 (CDM-R) Metal halide

**3024** Spot Light 10°



35W G8.5 CDM-TC Metal halide

**3056** Flood Light 40°

35W G8.5 CDM-TC Metal halide

With Integral Electronic ballast.

IP66



### Mini-Bullet with Extended Arm

**3175** 50W 230/12V GU5.3 MR16

With Integral Electronic transformer.

IP66

**3176** 50W 230V E27 PAR20 Halogen

**3177** 35W E27 PAR20 (CDM-R) Metal halide

IP66


**3178** Spot Light 10°

**3179** Flood Light 40°


35W G8.5 CDM-TC Metal halide

With Integral Electronic ballast.


IP66



Art. 3175, 3176



Art. 3177, 3178, 3179



### Accessories



Visor in Aluminum

**2329** For Bullet

**2328** For Mini-Bullet

Available in colours 10, 29



Spike in Aluminum

**2330** For Bullet

**2322** For Mini-Bullet

Available in colour 10



DMX Switchboard

**2975**

Power supply : 220-240V 50/60Hz  
Installation : Plastic recessing box included  
IP rate : IP 40  
Control signal : DMX512  
Control channel : 60 channel  
For details, please see p.286



IP65 Extension signal cable  
for RGB with M/F connector


**2478** Length: 1000

**2479** Length: 2000



Coloured Filters

Available in colours 25, 42, 55, 85



Refractor

Available in colour 41

