

Arena Due

Designed by Franco Mirenzi (Registered)



Body

Track mounted spotlight with luminaire body and driver box in cast aluminium.

Available with 3 circuit universal track adapter or Dali track adapter. Luminaire body designed with integrated heat-sink for a passive heat dissipation.

Versatile aiming angle tiltable vertically 0°-90° and rotatable horizontally 350°. Possibility to lock the fixture at the desired tilt angle.

LED sources

Citizen CLU series. SORAA SLE Optical Light Engine. CRI: 90, 95 | CCT: 3000K, 4000K. Other CRI and CCT optionsv available on request.

Optic

Narrow, medium and wide beam angle available.

Driver

Supplied with no-dimable driver. Dimming Options: 0-10V Dim, DALI, Phase, CASAMBI.

Applications

A modern design consisting of simple cylinders to act as heat management for the purpose to meet the highest requirements of the latest advanced lighting technology. Application areas: retail, museums, hospitality, residential, offices, lobbies.

Related Products

Recessed

P.70



MultiArena Recessed

P.72



Arena Due Surface

P.192




Finish

Powder coat in white or grey colour.

Accessories

No accessories available.





Arena Due


















Arena Due 70 / 130

Track









ø 130



Code ordering example: <u>6 2 7 6 B C 3 1 - 9 0 3 0 1 9 D 0 1 1 1</u>

	Product Code	Light Source Code*		>CRI	CCT**	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options		Finish
Arena Due 70	6276	BC31 Citizen	СОВ	90	30 3000K	6W	616 lm	19 / 24 / 34	D0	No Dim	11 White
Track					40 4000K		643 lm		DA	Dali Dim	75 Grey
									DP	Phase Dim	
Arena Due 130 Track	6274	BC22 Citizen	СОВ	_		12W	1552 lm	19 / 24 / 34	DO	No Dim	
							1577 lm		DA	Dali Dim	
		BS12 Soraa	SLC-16	95		8.7W	524 lm	10	DP	Phase Dim	
							547 lm		DC	CASAMBI	
						9.8W	739 lm	15 / 25 / 36	D1	0-10V Dim	
							775 lm				

Notes:

- * For complete code ordering information, please see page 377.
- ** For other CCT options, please contact us.