



Arena

Surface 70 | 130



Body

Wall/ceiling mounted luminaire with light body in cast aluminium designed with integrated heat-sink for a passive heat dissipation. Available in two sizes.

Equipped with pull-out mechanism, tiltable vertically 0-90° and rotatable horizontally 350°. Fixture can be easily locked at the chosen angle.

Accessories

No accessories available.

Finish

Powder coat in white or grey colour.

LED sources

Citizen CLU series. SORAA SLE Optical Light Engine.
CRI: 90, 95 | CCT: 3000K, 4000K.
Other CRI and CCT options available on request.

Optic

Lens.
Narrow, medium and wide beam angle available.

Driver

Driver canopy supplied with No-dimable driver.
Dimming Options: 0-10V Dim, DALI, Phase, CASAMBI.

Applications

Its crisp high tech design integrates well with virtually any interior while offering excellent aiming flexibility. When mounted on the wall it makes an ideal indirect light fixture. Application areas: museums, retail, hospitality, office lobbies.

Related Products


Arena Recessed
P.70



MultiArena Recessed
P.72



Arena Due Track
P.154









Arena



Arena 70 / 130

Surface



Code ordering example: **1 1 5 2 B C 3 1 - 9 0 3 0 1 9 D 0 1 1**

	Product Code	Light Source Code*	>CRI	CCT**	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options	Finish
Arena 70 Surface	1152	BC31 Citizen COB	90	30 3000K	6W	616 lm	19 / 24 / 34	D0 No Dim	11 □ White
				40 4000K		643 lm		DP Phase Dim	75 ■ Grey
Arena 130 Surface	1151	BC22 Citizen COB	95		12W	1552 lm	19 / 24 / 34	D0 No Dim	
						1577 lm		DA Dali Dim	
					8.7W	524 lm	10	DP Phase Dim	
						547 lm		DC CASAMBI	
		BS12 Sora	SLC-16		9.8W	739 lm	15 / 25 / 36	D1 0-10V Dim	
						775 lm			

Notes:

* For complete code ordering information, please see page 377.

** For other CCT options, please contact us.

