

Concept O


Armaturhus:

Extruderet aluminium

Overfladebehandling:

Pulverlakeret

Afskærmning:

Polycarbonat

Lyskilde:

LED 3000K CRI >80

Forventet levetid:


65.000T/L80, B10, Ta:25°C

LED driver:


200-240 VAC/50/60 Hz



EN 60598-1, EN 60598-2-2



Dimensioner (mm)	Hulmål (mm)	vægt (kg)
Ø650x85	6,4	
Ø950x85	7,0	
Ø1250x85	8,4	
Ø1550x85	10,6	
Ø1950x85	11,2	



URG	W	Lm	Lm/W	n(%)
Opal afskærmning				
<16	39	5640	78	54
<19	56	8460	79	52
<19	73	11280	80	52
<19	89	14100	78	49
--	112	16920	--	--
Microprismatisk polycarbonat plus				
<16	39	5640	69	48
<16	56	8460	73	48
<16	73	11280	74	48
<16	89	14100	70	44
--	112	16920	--	--
Microprismatisk polycarbonat				
<16	39	5640	88	61
<16	56	8460	89	59
<16	73	11280	90	58
<16	89	14100	86	54
--	112	16920	--	--

Tilbehør:

- ◆ loftroset
- ◆ forsyningskabel (2 tykkelser)
- ◆ centreret loftroset
- ◆ ophæng

Skal specificeres ved køb:

- ◆ afskærmning
- ◆ farve på armaturhus
- ◆ Kelvin (standard 3000K)
- ◆ dæmpbar driver
- ◆ dynamisk hvid LED
- ◆ 1 ell 3T nødbelysning