




BS8130ID CL8_24WW


Small cup track



1x COB LED max800lm 2700k



A A+ A++



NON DIMMABLE

WH	24°	10W	BS81301A CL8_24 WW
BLK	24°	10W	BS81302A CL8_24 WW
GR	24°	10W	BS81303A CL8_24 WW
BLK/CHR	24°	10W	BS81305A CL8_24 WW

DALI DIMMABLE

WH	24°	10W	BS81301D CL8_24 WW
BLK	24°	10W	BS81302D CL8_24 WW
GR	24°	10W	BS81303D CL8_24 WW
BLK/CHR	24°	10W	BS81305D CL8_24 WW

HONEYCOMB D50	BS0298
SQUARE OPTIC LENS	BS0383
LINEAR SPREAD LENS	BS0384

ALTERNATIVE LIGHT COLOUR		REPLACE WW BY
WARM WHITE	2700K	WW
NEUTRAL WHITE	3000K	NW
COLD WHITE	4000K	CW
DIM TO WARM	2200K-3000K	DW


! 15° or 38° or 60° beam angle on request > ref=..._15 or ..._38 or..._60
 ! DALI version can only be used in combination with DALI track system on page 342



1x MR16 ≤ 50W / LED MR16 12V



C A A+ A++



WH
BLK
GR
BLK/CHR

BS1301 |
BS1302 |
BS1303 |
BS1305 |



! Can be combined with cone accessory






BS1331

Cup
track

1x QRIII OPTILED max800lm 2800k



A A+ A++



NON DIMMABLE

WH	[20°]	11W	BS1331A OL8_20 WW
BLK	[20°]	11W	BS1332A OL8_20 WW
GR	[20°]	11W	BS1333A OL8_20 WW
BLK/CHR	[20°]	11W	BS1335A OL8_20 WW

DALI DIMMABLE

WH	[20°]	11W	BS81331D OL8_20 WW
BLK	[20°]	11W	BS81332D OL8_20 WW
GR	[20°]	11W	BS81333D OL8_20 WW
BLK/CHR	[20°]	11W	BS81335D OL8_20 WW


! 45° beam angle on request > ref= ..._45
! DALI version can only be used in combination with DALI track system on p.342



1x QRIII ≤ 100W



C A A+ A++



WH		BS1331
BLK		BS1332
GR		BS1333
BLK/CHR		BS1335

