



Fronteluce 90

Multi system linear projector



Body

Linear projector with light housing in aluminium extrusion. End caps and mounting brackets in cast aluminium.

Product inclusive of toughened safety glass, weatherproof durable silicone gasket, breather device and external screws made of stainless steel.

Front cover in hinged aluminium frame designed to avoid accumulation of dust and water.

Electrical installation includes double cable entry. Available in two sizes.

Light adjustable vertically up to 195° and horizontally 0-35°.

Accessories

Mounting brackets, suspension set, pole mounted bracket sets, wall sets, billboard sets, IP68 fast connector, IP65 extension cable.

Finish

Superior polyester powder coat in grey colour.

LED sources

Nichia single power led; Lextar SMD.
CRI: 80 | CCT: 3000K, 4000K.RGB/W, TuneableWhite.

Other CRI and CCT options available on request.

Optic

Frosted glass diffuser or lens, according with the chosen model.

Driver


Supplied with integrated no-dimmable driver.
Dimming Options: 0-10V Dim, DALI, Phase, CASAMBI.

Applications


Extremely compact linear luminaire offering minimal visual impact and huge flexibility. A vast range of accessories makes possible to mount it in many different way (ground, ceiling, wall, pole). Application areas: facades, under canopy areas, billboards, sculptures, art installations.

Related Products

Forlinea
P.348




Fronteluce 90




Fronteluce 90

Surface



Fronteluce 90 Opal diffuser

Surface


 Code ordering example: **3 1 9 8 B N 1 1 - 8 0 3 0 2 5 D 0 2 9**

	Product code	Light source code*	Length (L)	>CRI	CCT**	LED Power	Nominal Lumen	Beam angle (BA°)	Driver Options	Finish
Fronteluce 90	3198	BN11 Nichia 3535	600	80	30 3000K	12 x 3W	1500 lm	25	D0 No Dim	29 Grey (Outdoor)
					40 4000K		DX DMX			
	3199		900			18 x 3W	2250 lm		DA Dali Dim	
							2700 lm		D1 0-10 Dim	
	3200			1200			24 x 3W	3000 lm		DP Phase
								3600 lm		DC CASAMBI
TW TW 1800K to 6000K							12 x 3W /	00		DX DMX
RG B0							/ /			DC CASAMBI
Fronteluce 90 Opal diffuser	3486	BT11 Lextar SMD	600	80	30 3000K	40W	2400 lm	EW (00)	D0 No Dim	
					40 4000K		2600 lm		DX DMX	
	3487		900			60W	3600 lm		DA Dali Dim	
							3900 lm		D1 0-10 Dim	
	3488		1200			80W	4800 lm		DP Phase	
						5200 lm		DC CASAMBI		

Notes:

* For complete code ordering information, please see page 377.

** For other CCT options, please contact us.

For related accessories, please see page 354-355.

 EW = Extra Wide. Ordering code: **00**.



Accessories



Product / Accessories

Mounting brackets

Available in colour 29

2 pcs. adjustable.

Mounting brackets

Available in colour 29

2 pcs. adjustable.

Mounting brackets

Available in colour 29

2 pcs. adjustable and extendable.

Suspension set

Available in colour 29

2 pcs. 1500mm wire hangers and one power supply cable.

Fronteluce 90









2379

2380

2381

2382

Fronteluce 90 Opal diffuser



Product / Accessories

Pole mounted bracket set

Available in colour 29

Ø 102 mm Ø 120 mm

For one fixture

Pole mounted bracket set

Available in colour 29

Ø 102 mm Ø 120 mm

For two fixtures

Wall mounted set

Available in colour 29

Billboard set

Available in colour 29

For one banner

Fronteluce 90

2394

2395

2565




2566

2567

2568

2569

Fronteluce 90 Opal diffuser




Notes:

For complete code ordering information, please see page 377.





Accessories



Product / Accessories

Billboard set

Available in colour 29

Ø 102 mm Ø 120 mm
suitable for two banners.

Extension signal cable

L: 1000 L: 2000

For RGB with M/F connectors.

Fast connector M20

IP68

(\varnothing 6 ÷ 12 mm)

Fronteluce 90

2570


2571

2478

2479

2577

Fronteluce 90 Opal diffuser



Notes:

For complete code ordering information, please see page 377.

