



Galaxis Pro

Recessed 165 | 200 | 230



Body

Round mounting trim in cast aluminium with springs for trim installation on a ceiling thickness of max. 25mm.

Luminaire body and heat dissipator for passive cooling in cast aluminium. Secondary reflector is precision formed from highly reflective pure aluminium.

Available in three different sizes.

LED sources

Samsung SMD LED.
CRI: 90 | CCT: 3000K, 4000K.
Other CRI and CCT options, Tuneable White and DimToWarm versions available on request.
Emergency versions available upon request.

Optic

Equipped with acrylic diffuser. Lens in PMMA. Wide beam angle available.

Related Products

**DomoLED
Recessed**
P.128



Accessories

No accessories available.

Driver

Supplied with No-dimable remote driver.
Dimming Options: 0-10V Dim, DALI, Phase, CASAMBI.

Finish

Powder coat in black or white colour.

Applications

Provide a visual comfortable energy-efficient with a wide uniform general lighting solution, also ideal for use in under canopy or bathroom locations.

Application areas: offices, corridors, canopies hospital, hotels.





Galaxis Pro




Galaxis Pro 165 / 200 / 230


Fixed





Ø 150



Ø 180



Ø 205



Code ordering example: **R K 1 5 B M 1 1 - 9 0 3 0 7 5 D 0 1 0**

	Product Code	Light Source Code*	>CRI	CCT**	LED Power	Nominal Lumen	Beam Angle (BA°)	Driver Options	Finish
Galaxis Pro 165 Fixed	RK15 ● BM11	SumSung SMD	90	30 3000K	22W	2574 lm	75	D0 No Dim	10 ■ Black
				40 4000K		2726 lm		DA Dali Dim	11 □ White
Galaxis Pro 200 Fixed	RK13 ●				33W	3784 lm		DP Phase Dim	
						4004 lm		DC CASAMBI	
Galaxis Pro 230 Fixed	RK12 ●				45W	4983 lm		D1 0-10V Dim	
						5269 lm			

Notes:

- * For complete code ordering information, please see page 377.
- ** For other CCT options, please contact us.

