



FO99202D CL8_24WW



FO99201D CL8_24WW



1x **COB LED** max1500lm 3000k



NON DIMMABLE

WH	30°	11W	BB99201A CL12_30 NW
BLK	30°	11W	BB99202A CL12_30 NW

DALI DIMMABLE

WH	30°	11W	BB99201D CL12_30 NW
BLK	30°	11W	BB99202D CL12_30 NW

HONEYCOMB D70 BS0297

ALTERNATIVE LIGHT COLOUR REPLACE NW BY

WARM WHITE	2700K	WW
NEUTRAL WHITE	3000K	NW
MEDIUM WHITE	3500K	MW
COLD WHITE	4000K	CW
DIM TO WARM	2200K-3000K	DW


! 15° beam angle on request > ref= ...15

! DALI version can only be used in combination with DALI track system on p.342



Small steamer adaptor track

1x **CONE COB LED** max800lm 2700k



NON DIMMABLE

WH	24°	10W	FO99201A CL8_24 WW
BLK	24°	10W	FO99202A CL8_24 WW

DALI DIMMABLE

WH	24°	10W	FO99201D CL8_24 WW
BLK	24°	10W	FO99202D CL8_24 WW

HONEYCOMB D50 BS0298
SQUARE OPTIC LENS BS0383
LINEAR SPREAD LENS BS0384

ALTERNATIVE LIGHT COLOUR REPLACE WW BY

WARM WHITE	2700K	WW
NEUTRAL WHITE	3000K	NW
COLD WHITE	4000K	CW
DIM TO WARM	2200K-3000K	DW

! 15° or 38° or 60° beam angle on request > ref=...15 or ...38 or...60

! DALI version can only be used in combination with DALI track system on p.342





YUP hotel by Differenthotels
Concept and Interior By Caneau International
Photography By Hugo Thomassen






Small steamer adaptor track

1x MR16 ≤ 50W / LED MR16 12V

C A A+ A++



WH
BLK


BB9201 |
BB9202 |

! Can be combined with cone accessory



1x CONE COB LED max700lm 2700k

A A+ A++



NON DIMMABLE

WH	30°	7W		BB89201A CL7_30 WW
BLK	30°	7W		BB89202A CL7_30 WW

DALI DIMMABLE

WH	30°	7W		BB89201D CL7_30 WW
BLK	30°	7W		BB89202D CL7_30 WW

ALTERNATIVE LIGHT COLOUR

WARM WHITE	2700K
NEUTRAL WHITE	3000K

REPLACE WW BY

WW
NW

! DALI version can only be used in combination with DALI track system on p.342



1x QR70 ≤ 50W

C




WH
BLK

BB9211 |
BB9212 |



1x GU10 ≤ 50W / LED GU10 (max height 55mm)

C A A+ A++



WH
BLK

BB9221 |
BB9222 |

! Can be combined with cone accessory





BB99631D CL20_24NW

Steamer adaptor


track



1x CONE COB LED max2400lm 3000k



A A⁺ A⁺⁺



NON DIMMABLE

WH	[24°]	18W	BB99631A CL20_24 NW
BLK	[24°]	18W	BB99632A CL20_24 NW

DALI DIMMABLE

WH	[24°]	18W	BB99631D CL20_24 NW
BLK	[24°]	18W	BB99632D CL20_24 NW

HONEYCOMB D76 BS0296

ALTERNATIVE LIGHT COLOUR REPLACE NW BY

WARM WHITE	2700K	WW
NEUTRAL WHITE	3000K	NW
MEDIUM WHITE	3500K	MW
COLD WHITE	4000K	CW
DIM TO WARM	2200K-3000K	DW

! 40° beam angle on request > ref= ...40

! CRI 80+ available on request > change ref BB9...to BB8...

! COB specials on request (CrispWhite, food, ...)

! DALI version can only be used in combination with DALI track system on p.342



1x COB LED max3500lm 3000k



A A⁺ A⁺⁺



NON DIMMABLE

WH	[24°]	26W	BB99631A CL30_24 NW
BLK	[24°]	26W	BB99632A CL30_24 NW

DALI DIMMABLE

WH	[24°]	26W	BB99631D CL30_24 NW
BLK	[24°]	26W	BB99632D CL30_24 NW

ALTERNATIVE LIGHT COLOUR REPLACE NW BY

WARM WHITE	2700K	WW
NEUTRAL WHITE	3000K	NW
MEDIUM WHITE	3500K	MW
COLD WHITE	4000K	CW
DIM TO WARM	2200K-3000K	DW

! 17° and 36° beam angle on request > ref= ...17 or ...36

! CRI 80+ available on request > change ref BB9...to BB8...

! COB specials on request (CrispWhite, food, ...)

! DALI version can only be used in combination with DALI track system on p.342






Steamer adaptor track

1x QRIII OPTILED max800lm 2800k



A A+ A++



IGBT/TRIAC DIMMABLE

WH	20° 12W	BB89601C OL8_20 WW
BLK	20° 12W	BB89602C OL8_20 WW

DALI DIMMABLE

WH	20° 12W	BB89601D OL8_20 WW
BLK	20° 12W	BB89602D OL8_20 WW


! 45° beam angle on request > ref= ..._45
! DALI version can only be used in combination with DALI track system on p.342



1x QRIII ≤ 100W



C A A+ A++



WH		BB9601
BLK		BB9602

! Can be combined with cone accessory







Loft & Lys ApS

... løsninger med højt til loftet



Loft & Lys ApS

Værkstedsgården 9 ♦ DK-2620 Albertslund ♦ Denmark ♦ +45 6080 2973 ♦ www.loftlys.dk ♦ email: info@loftlys.dk