

Flat roof cover without stairs

Flat roof covers from Roto are energy-efficient solutions for refurbishing old space-saving stairs from all well-known manufacturers.



Energy label

- Top cover: 0.68 W/m²K*
- * calculated by manufacturer according to DIN EN ISO 6946



Energy efficiency

- Air permeability Class 4 certified*
- * certified by IFT Rosenheim according to DIN EN 12207 / 12114
- Circumferential seal
- Thermal insulation in the cover



Upper cover

- Metal flashing with galvanised sheet steel
- Aluminium sheet for opening widths of 90 cm and above**
- Closure using Roto NX hardware
- Edge glued for protection against weather
- Incl. rubber hollow profile seal (double) with contact profile for roof membrane
- Impermeable to driving rain (Class E1200)
- Stop on right as standard



Hatchbox

- White
- Water-repellent
- Including additional treads in the hatchbox
- Installation allowance: 2 cm



Ready-to-install with standard accessories

- Mounting screws
- Professional installation package (see page 78) **NEW**



Note

Not possible for "automatic opening" version (open/close upper and lower cover at the same time).



Ideal for combining with the extension ladder



Made to measure

	PG 1	PG 2
Opening length	75 - 140	140.1 - 250
Opening width	60 - 90	90.1 - 120
Box height	25 - 117	40 - 117
Roof thickness	- 15 less than box height	

**Surcharge: € 419 for aluminium sheet

Accessories

Electric flat roof cover From box height of 40 cm and above	From page 70 onwards (No. 31)	
Cover heating	From page 70 onwards (No. 25)	
Upper cover with lock case prepared for profile cylinder	From page 70 onwards (No. 9a)	
Upper cover with lock case with profile cylinder fitted	From page 70 onwards (No. 9b)	

Options

Improved thermal insulation - U value of upper cover 0.38 W/m ² K - customer-provided insulation max. 80 mm	
Improved thermal insulation - U value of upper cover 0.31 W/m ² K - customer-provided insulation max. 100 mm	

