



Vertical retractable stairway

This model has been specifically developed for vertical installation. It is manufactured from high-quality aluminium pressure die-cast and is therefore extremely strong and very light to handle. The dead weight of the stairway is additionally dampened in the end position by a gas strut.



Energy label

- Component: 0.58 W/m²K*
- * calculated by manufacturer according to DIN EN ISO 6946



Energy efficiency

- Circumferential seal
- Thermal insulation in the cover



Hatchbox / cover

- White hatchbox
- White hatch cover
- Box depth: 24 cm
- Installation allowance 2 cm
- Stainless steel towing eyelet



Stairs

- Aluminium retractable stairways
- Treads: 20-35 cm, 14 cm deep (made of pressure die-casting)
- Load bearing 200 kg per tread



Ready-to-install with standard accessories

- Telescopic handrail included
- Mounting screws
- Operating pole
- Snap-on white covering strips (plastic)





Made to measure

Clear room height / number of treads	Price group			
up to 339 / 12				PG 4
up to 309 / 11			PG 3	
up to 279 / 10		PG 2		
220 - 250 / 9	PG 1			
Height*	80	85	95	105 - 149
Width*	60 - 100			
Box depth	24 - 40			

* Minimum dimension of the provided opening

Accessories

Retractable stairway coating in RAL colours	From page 70 onwards (No. 6)	
Convenience tread (additional tread)	From page 70 onwards (No. 22b)	

