



## Retractable stairway **Piccolo**

Our retractable stairway package made of aluminium profiles has been developed for installation in very small ceiling openings or in existing hatchboxes. The retractable stairway package is delivered with installation accessories in the box.



### Stairs

- Aluminium retractable stairways
- Treads: 28-33 cm, 8 cm deep (profile treads)
- Load bearing 150 kg per tread



### Ready-to-install with standard accessories

- Operating pole



NO pivot range necessary

## Made to measure

Clear room height / number of treads	Price group			
up to 290 / 12				PG 4
up to 265 / 11			PG 3	
up to 240 / 10		PG 2		
from 200 to 215 / 9	PG 1			
Opening length (starting)	51	55	58	62
Opening width (min)	37			

## Accessories

Cover suspension for on-site hatch cover (max. weight 20 kg) (minimum dimensions change - opening length of at least 75 cm)	From page 70 onwards (No. 21)	
Telescopic handrail from 80 cm opening length upwards can be supplied	From page 70 onwards (No. 3)	





## Retractable stairway **Piccolo Premium**

The Piccolo Premium is the "little sister" of our Junior retractable stairway and is the ideal solution for retro fitting during renovation. It is easily installed into ready formed openings in the ceiling or can be fixed onto vertical faces such as mezzanine floors.



### Stairs

- Aluminium retractable stairways
- Treads: 28-33 cm, 8 cm deep (profile treads)
- Load bearing 150 kg per tread



### Ready-to-install with a wide range of accessories

- Attachment element: White coated, 11 cm high
- Operating pole
- Fascia
- 18 x 340 x 110 mm
- 18 x 390 x 110 mm



## Made to measure

Clear room height / number of treads	Price group			
up to 300 / 12				PG 4
up to 275 / 11			PG 3	
up to 250 / 10		PG 2		
from 200 to 225 / 9	PG 1			
Opening length (starting)	55	62	66	70
Opening width (min)	36			

Can be combined with wooden hatch Designo (see page 53)  
NOTE: 15 cm less in terms of width when installed in an empty hatch box

## Accessories

Wrapping tape (minimum dimensions change: width +3 cm, height +16 cm)	From page 70 onwards (No. 18)	
Cover suspension for on-site hatch cover (max. weight 20 kg) (minimum dimensions change - opening length of at least 75 cm)	From page 70 onwards (No. 21)	
Telescopic handrail	From page 70 onwards (No. 3)	

