



## 402201 HYDROCUBE 01 LED




Square up or down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered frosted safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 3 x CREE XT-E LED. IP65 rating.



### Energy Label **A++**

- Material: high corrosion resistance extruded copper-free aluminum body and fixing arms.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x CREE "XT-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
7.5 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	MONO DIRECTIONAL DIFFUSED	340	45.33	TEXTURED GREY

## 402202 HYDROCUBE 02 LED




Square up and down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered frosted safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 6 x CREE XT-E LED. IP65 rating.



### Energy Label **A++**

- Material: high corrosion resistance extruded copper-free aluminum body and fixing arms.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 x CREE "XT-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X7.5 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	BI-DIRECTIONAL DIFFUSED	2 X 340	45.33	TEXTURED GREY



