

Concept O /E



White	W	Golden eye	Q
Gray	G	Schala	Q
Black	S	Kuburn	L
Blue	U	Rusty chain	R
Green	V	Pure concrete	C
Yellow	T	Mat	T
Red	K	Dark oak	Q
Jungle	N	Carbon	I




Ø676



Ø976



Ø1276



EN 60598-1, EN 60598-2-2


Armaturhus:

Extruderet aluminium

Overfladebehandling:

Pulverlakeret

Afskærmning:

Polycarbonat

Lyskilde:

LED 3000K CRI >80

Forventet levetid:

65.000T/L80, B10, Ta:25°C

LED driver:

200-240 VAC/50/60 Hz

Dimensioner (mm)	Hulmål (mm)	vægt (kg)
Ø676x100	Ø660/510	7,3
Ø976x100	Ø960/810	12,0
Ø1276x100	Ø1260/1110	18,0

URG	W	Lm	Lm/W	n(%)
Opal afskærmning				
<16	39	5640	78	54
<16	56	8460	79	52
<16	73	11280	80	52
Microprismatisk polycarbonat plus				
<16	39	5640	69	48
<16	56	8460	73	48
<16	73	11280	74	48
Microprismatisk polycarbonat				
<16	39	5640	88	61
<16	56	8460	89	59
<16	73	11280	90	58

Skal specificeres ved køb:

- ◆ afskærmning
- ◆ farve på armaturhus
- ◆ Kelvin (standard 3000K)
- ◆ dæmpbar driver
- ◆ dynamisk hvid LED
- ◆ 1 ell 3T nødbelysning