



ARCHITECTURAL
LIGHTING

ROFY 60 Sq D/I



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source


LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear


LED driver 220-240V-50/60Hz included






01. Select version

ROFY 60 Sq D/I




gCONTROL+ - Microprismatic diffuser (75%/25%)



UGR	W	lm output	lm/W	LxWmm	CODE*
≤16	18	2231	124	286x286	90714L286▼▲◆◆00
≤19	60	7753	129	550x550	90714L550▼▲◆◆00
≤19	33	3967	120	550x286	90714L552▼▲◆◆00
≤19	48	6269	131	814x286	90714L812▼▲◆◆00
≤19	60	7935	132	1078x286	90714L102▼▲◆◆00
≤19	75	9912	132	1342x286	90714L132▼▲◆◆00

LIGHT+ - Opal diffuser (75%/25%)



UGR	W	lm output	lm/W	LxWmm	CODE*
≤22	18	2325	129	286x286	90716L286▼▲◆◆00
≤22	60	8081	135	550x550	90716L550▼▲◆◆00
≤22	33	4135	125	550x286	90716L552▼▲◆◆00
≤22	48	6534	136	814x286	90716L812▼▲◆◆00
≤22	60	8270	138	1078x286	90716L102▼▲◆◆00
≤22	75	10330	138	1342x286	90716L132▼▲◆◆00

ROFY 60 Sq D/I

- To complete the product add current supply cable, suspension and ceiling rose. Please order separately.
- In order to guarantee total light uniformity on the ceiling in the suspended version, installation must be carried out at a minimum distance of 500 mm.



*Replace the symbols to complete the code

Control gear	Symbol
HF	E
DALI	H

Colour 1	Symbol
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	Symbol
No EM	0
EM 3h (K3) 2	3

Colour temp.	Symbol
3000K	3
4000K	0
Tunable White	T





02. Select options

OPTIONS Code*

Suspension


S11 L1500 mm (x4)	9129041
S11 L3000 mm (x4)	9129042
S11 L6000 mm (x4)	9129043


Transparent current supply cable

L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L1500 mm - 7 x 0,75 mm ²	940600
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L3000 mm - 7 x 0,75 mm ²	940601
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507
L6000 mm - 7 x 0,75 mm ²	940602

• For the DALI option with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm².

Ceiling rose

Surface mounted T25	45  \varnothing 100	978610♣
Surface mounted T29 (DALI+K3)		978611♣

Recessed T7	 \varnothing 70 35 \varnothing 90	971400♣
Recessed T59 (DALI+K3)		971410♣

Low Output version

• Under request.



***Replace the symbols to complete the code**

Colour


<input type="checkbox"/> White	W
<input checked="" type="checkbox"/> Black	B



Product details



Ceiling surface application



Suspended application



Wall mounted



Indirect light



gCONTROL+ diffuser



LIGHT+ diffuser



Outer parallel suspension



Ceiling roses

