



ARCHITECTURAL  
LIGHTING

## ROFY 60 /T



### Product characteristics

**Body**

Aluminium

**Finish**

Powder coated

**Optical system**

gCONTROL+ - Microprismatic diffuser  
LIGHT+ - Opal diffuser

**Light source**

LED, RG1, CRI>80, MacAdam Step ≤3

**LED lifetime**


80.000h @ L90, B10, Ta 25°C

**Control gear**

LED driver 220-240V-50/60Hz included

**Ceiling thickness**

For ceilings between 9,5-18 mm






## 01. Select version

### ROFY 60 /T




#### gCONTROL+ - Microprismatic diffuser



UGR	W	lm output	lm/W	Dmm	Ø	Ø	CODE*
≤22	16	1945	122	Ø300	Ø331		90559L300▼▲◆◆00
≤22	24	3085	129	Ø400	Ø427		90559L400▼▲◆◆00
≤19	43	5939	138	Ø600	Ø630		90559L600▼▲◆◆00
≤19	65	8844	136	Ø900	Ø927		90559L900▼▲◆◆00
≤19	107	14432	135	Ø1150	Ø1179		90559L115▼▲◆◆00

#### LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	Dmm	Ø	Ø	CODE*
≤22	16	2135	133	Ø300	Ø331		90561L300▼▲◆◆00
≤25	24	3385	141	Ø400	Ø427		90561L400▼▲◆◆00
≤22	43	6516	152	Ø600	Ø630		90561L600▼▲◆◆00
≤22	65	9704	149	Ø900	Ø927		90561L900▼▲◆◆00
≤22	107	15835	148	Ø1150	Ø1179		90561L115▼▲◆◆00

### ROFY 60 /T

- This product cannot be installed on the wall.



\*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour 1	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) 2	3

Colour temp.	
3000K	3
4000K	0
Tunable White 3	T

## 02. Select options

### OPTIONS


**Steel safety cable**  
L1500 mm Code 955000

#### Low Output version

- Under request.



### Product details



Trimless application



gCONTROL+ diffuser



LIGHT+ diffuser

