



ARCHITECTURAL
LIGHTING

ROFY 60 /T D/I



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included

Ceiling thickness


For ceilings between 9,5-18 mm






01. Select version

ROFY 60 / T D/I




gCONTROL+ - Microprismatic diffuser (80%/20%)



UGR	W	lm output	lm/W	Dmm	Φ	CODE*
≤19	32	3683	115	Ø400	Ø523	90591L400▼▲0♦00
≤19	56	6869	123	Ø600	Ø723	90591L600▼▲0♦00
≤19	84	10270	122	Ø900	Ø1023	90591L900▼▲0♦00
≤19	137	16846	123	Ø1150	Ø1273	90591L115▼▲0♦00

LIGHT+ - Opal diffuser (80%/20%)



UGR	W	lm output	lm/W	Dmm	Φ	CODE*
≤22	32	3851	120	Ø400	Ø523	90593L400▼▲0♦00
≤22	56	7182	128	Ø600	Ø723	90593L600▼▲0♦00
≤22	84	10736	128	Ø900	Ø1023	90593L900▼▲0♦00
≤22	137	17612	129	Ø1150	Ø1273	90593L115▼▲0♦00

ROFY 60 / T D/I

• This product cannot be installed on the wall.



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) ²	3

Colour temp.	
3000K	3
4000K	0
Tunable White	T

02. Select options

OPTIONS Code

Tilted bracket

Ø400 mm	927100
Ø600 mm	927101
Ø900 mm	927102
Ø1150 mm	927103

Steel safety cable

L1500 mm	955000
----------	--------

Low Output version

• Under request.



Product details



Trimless application



Tilted bracket



gCONTROL+ diffuser



LIGHT+ diffuser

