



ARCHITECTURAL
LIGHTING

ROFY 85 /E



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime


80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included

Ceiling thickness

For ceilings between 1-25 mm






01. Select version

ROFY 85 / E




gCONTROL+ - Microprismatic diffuser



UGR	W	lm output	lm/W	Dmm	Φ	CODE*
≤19	16	1810	113	Ø300	Ø277	90622L300♥♣0♦00
≤19	24	2871	120	Ø400	Ø377	90622L400♥♣0♦00
≤19	43	5526	129	Ø600	Ø577	90622L600♥♣0♦00
≤19	65	8230	127	Ø900	Ø877	90622L900♥♣0♦00
≤19	107	13429	126	Ø1150	Ø1127	90622L115♥♣0♦00

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	Dmm	Φ	CODE*
≤25	16	2135	133	Ø300	Ø277	90621L300♥♣0♦00
≤25	24	3385	141	Ø400	Ø377	90621L400♥♣0♦00
≤22	43	6516	152	Ø600	Ø577	90621L600♥♣0♦00
≤22	65	9704	149	Ø900	Ø877	90621L900♥♣0♦00
≤22	107	15835	148	Ø1150	Ø1127	90621L115♥♣0♦00

ROFY 85 / E

• This product cannot be installed on the wall.



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) ²	3

Colour temp.	
3000K	3
4000K	0
Tunable White ³	T

02. Select options

OPTIONS Code


Steel safety cable 955000

Low Output version

• Under request.



Product details



Ceiling recessed application



gCONTROL+ diffuser



LIGHT+ diffuser

