



ARCHITECTURAL
LIGHTING

ROFY 85 IP /C



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

LIGHT+ - Opal diffuser

Light source


LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear


LED driver 220-240V-50/60Hz included






01. Select version

ROFY 85 IP /C



LIGHT+ - Opal diffuser



W	lm output	lm/W	Dmm	CODE*
16	2135	133	Ø300	90581L300♥♣♦0+00
24	3385	141	Ø400	90581L400♥♣♦0+00
43	6516	152	Ø600	90581L600♥♣♦0+00



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
<input type="checkbox"/> White	W
<input type="checkbox"/> Grey	G
<input type="checkbox"/> Black	B
<input type="checkbox"/> Sahara	0
<input type="checkbox"/> Mist	1
<input type="checkbox"/> Carbon	I
<input type="checkbox"/> Autumn	L
<input type="checkbox"/> Rusty chain	R
<input type="checkbox"/> Jungle	N
<input type="checkbox"/> Golden eye	D

Emergency	
No EM	0
EM 3h (K3) ²	3

Colour temp.	
3000K	3
4000K	0
Tunable White ³	T

02. Select options

OPTIONS

Low Output version

- Under request.



Product details



Ceiling surface application



Wall mounted



LIGHT+ diffuser



IP54 protection

