



ARCHITECTURAL
LIGHTING

ROFY 85 IP /E



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime


80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included

Ceiling thickness

For ceilings between 1-35 mm






01. Select version

ROFY 85 IP / E



LIGHT+ - Opal diffuser



W	lm output	lm/W	Dmm	Ø	Ø	CODE*
16	2135	133	Ø302	Ø286	Ø286	90573L300♥♣♦0♦00
24	3385	141	Ø402	Ø386	Ø386	90573L400♥♣♦0♦00
43	6516	152	Ø603	Ø586	Ø586	90573L600♥♣♦0♦00

ROFY 85 IP / E

• This product cannot be installed on the wall.



*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H

Colour ¹	▲
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	●
No EM	0
EM 3h (K3) ²	3

Colour temp.	◆
3000K	3
4000K	0
Tunable White ³	T

02. Select options

OPTIONS Code


Steel safety cable L1500 mm 955000

Low Output version

• Under request.



Product details



Ceiling recessed application



LIGHT+ diffuser

