

SPA D/I LED

ARCHITECTURAL LIGHTING

Norms

EN 60598-1 , EN 60598-2-1


Body: Extruded aluminium.

Finish: Powder coated.

Light source: LED 4000K, CRI>80.

LED life time: 65.000h @ L80, B10, Ta 25°C.

Control gear: LED driver 220-240VAC-50/60Hz.

DAM - Microprismatic diffuser | 80% (Direct) + 20% (Indirect)

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)	Kg	K1 K3	HF	DALI
	≤19	46	5690	94	76	875x315x88	8,6	• •	90108.L130.E	90108.L130.H
	≤19	58	7675	101	76	1150x315x88	11,2	• •	90108.L140.E	90108.L140.H
	≤19	69	9536	105	76	1425x315x88	13,6	• •	90108.L150.E	90108.L150.H
	≤19	57	7148	98	78	590x590x88	9,2	• •	90108.L410.E	90108.L410.H

DOZ - Opal polycarbonate diffuser | 80% (Direct) + 20% (Indirect)

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)	Kg	K1 K3	HF	DALI
	≤16	46	5690	92	74	875x315x88	8,6	• •	90100.L130.E	90100.L130.H
	≤16	58	7675	99	75	1150x315x88	11,2	• •	90100.L140.E	90100.L140.H
	≤16	69	9536	102	74	1425x315x88	13,6	• •	90100.L150.E	90100.L150.H
	≤19	57	7148	95	76	590x590x88	9,2	• •	90100.L410.E	90100.L410.H

DAM | DOZ

- To complete the product add suspension, current supply cable and ceiling rose. Please order separately.

OPTIONS

Finish

Order code	Order code
White W	Golden eye D
Gray G	Sahara 0
Black B	Autumn L
Blue U	Rusty chain R
Green V	Pure chocolate C
Yellow T	Mist 1
Red K	Dark rock 9
Jungle N	Carbon I


Colour temperature

Order code	Order code
3000K	3000


Ceiling rose

Order code	Order code
Square ceiling rose	
Surface mounted	9717
Recessed	9714

- To complete this option, please add ceiling rose colour.


Current supply cable

Order code	Order code
1,5m transparent cable 0,75mm ²	1,5m transparent cable 1,5mm ²
3x0,75mm ² 940400	7x1,5mm ² 940100
5x0,75mm ² 940500	9x1,5mm ² 941200


Emergency unit

Order code	Order code
Emergency unit 3 hours	K3
Emergency unit 1 hour	K1


- Test function by telecommand signal.


Suspension


Order code	Order code
Suspension type "I" (x4)	910002
Suspension type "Y" (x2)	910003


Low power version


Option supplied under request.

PHOTOMETRY


SPA D/I LED 57W DAM (590x590mm) 4000K



SPA D/I LED 69W DAM 4000K




SPA D/I LED 57W DOZ (590x590mm) 4000K




DIMENSIONS


590x590




875x315



1150x315



1425x315



TO SPECIFY

Suspended square or rectangular LED direct/indirect luminaire. Powder coated extruded aluminium body with round corners. Available in 4 sizes (875/1150/1425 x 315mm and 590x590mm) equipped with DAM microprismatic or DOZ opal polycarbonate diffuser. Standard version with LED 4000K, CRI>80 and 65.000h lifetime (@L80, B10, Ta 25°C). Optional 3000K, DALI dimmable driver and 1 or 3 hours emergency unit. Suspension, transparent current supply cable and surface or recessed ceiling rose as accessories. Available in 16 different colours – as Roxo Lighting SPA LED D/I

ROXO

