



SPA LED

ARCHITECTURAL LIGHTING



Norms

EN 60598-1, EN 60598-2-1



Body: Extruded aluminium.

Finish: Powder coated.

Light source: LED 4000K, CRI>80.

LED life time: 65.000h @ L80, B10, Ta 25°C.

Control gear: LED driver 220-240VAC-50/60Hz.

DAM - Microprismatic diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)	Kg	K1 K3	HF	DALI
	≤19	30	4080	107	79	875x315x88	8,1	• •	90030.L130.E	90030.L130.H
	≤19	39	5440	112	80	1150x315x88	10,6	• •	90030.L140.E	90030.L140.H
	≤19	47	6800	113	78	1425x315x88	12,5	• •	90030.L150.E	90030.L150.H
	≤19	39	5440	113	81	590x590x88	8,9	• •	90030.L410.E	90030.L410.H

DOZ - Opal polycarbonate diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC (mm)	Kg	K1 K3	HF	DALI
	≤22	30	4080	105	77	875x315x88	8,1	• •	90090.L130.E	90090.L130.H
	≤22	39	5440	109	78	1150x315x88	10,6	• •	90090.L140.E	90090.L140.H
	≤22	47	6800	109	75	1425x315x88	12,5	• •	90090.L150.E	90090.L150.H
	≤22	39	5440	109	78	590x590x88	8,9	• •	90090.L410.E	90090.L410.H

OPTIONS



Finish

Order code	Order code
White W	Golden eye D
Gray G	Sahara 0
Black B	Autumn L
Blue U	Rusty chain R
Green V	Pure chocolate C
Yellow T	Mist 1
Red K	Dark rock 9
Jungle N	Carbon I



Colour temperature

Order code	Order code
3000K	3000



Ceiling rose

Order code
Square ceiling rose
Surface mounted 9717
Recessed 9714

• To complete this option, please add ceiling rose colour.



Current supply cable

Order code	Order code
1,5m transparent cable 0,75mm ²	1,5m transparent cable 1,5mm ²
3x0,75mm ² 940400	7x1,5mm ² 940100
5x0,75mm ² 940500	9x1,5mm ² 941200



Emergency unit

Order code	Order code
Emergency unit 3 hours	K3
Emergency unit 1 hour	K1

• Test function by telecommand signal.



Suspension


Order code
Suspension type "I" (x4) 910002
Suspension type "Y" (x2) 910003




Low power version

Option supplied under request.


PHOTOMETRY



SPA LED 39W DAM (590x590mm) 4000K



SPA LED 47W DAM 4000K




SPA LED 39W DOZ (590x590mm) 4000K






DIMENSIONS


590x590




875x315



1150x315



1425x315



TO SPECIFY

Surface or suspended square or rectangular LED luminaire. Powder coated extruded aluminium body with round corners. Available in 4 sizes (875/1150/1425 x 315mm and 590x590mm) equipped with DAM microprismatic or DOZ opal polycarbonate diffuser. Standard version with LED 4000K, CRI>80 and 65.000h lifetime (@L80, B10, Ta 25°C). Optional 3000K, DALI dimmable driver and 1 or 3 hours emergency unit. Suspension, transparent current supply cable and surface or recessed ceiling rose as accessories. Available in 16 different colours – as Roxo Lighting SPA LED

