



Stella 66



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Storehouses, Industrial and Commercial areas. Corridors, Garages, Basements.

Mounting: Surface/Wall Mounted.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>80, MacAdam Step<3, 50.000h life (@L80, B10, Ta 25°C).

Optical System: Diffuser: Opal polycarbonate.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Injected polycarbonate and polyurethane gasket.


Surface Finish: White matt powder coated gear tray.

Fixing system: Stainless steel fixing brackets and clips.

DC0 - Polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	D (mm)	K1	K3	Kg	HF	DALI
	14	2000	120	84	660x101x101	390	-	-	1,3	908E.106.12.F4	-
	29	4000	121	88	1277x101x101	800	•	•	2,2	908E.112.12.F4	908E.112.12.E4
	36	5000	124	89	1573x101x101	1100	•	•	2,7	908E.115.12.F4	908E.115.12.E4
	29	4000	114	83	660x145x101	390	-	-	1,9	908E.206.12.F4	908E.206.12.E4
	53	8000	127	84	1277x145x101	800	•	•	2,9	908E.212.12.F4	908E.212.12.E4
	66	10000	130	86	1573x145x101	1100	•	•	3,6	908E.215.12.F4	908E.215.12.E4

DIMENSIONS



Example code for order: 908E.112.12.E4 (DALI) + 3000 + PIR (OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





OPTIONS

Colour temperature



3000K

Order code
3000

Light and presence sensor



Light and presence sensor

Order code
PIR

Connector kit



KIT 3-pole IP68 connector
KIT 5-pole IP68 connector

Order code
966600
966610

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour

Order code
K3
K1

• Includes test function by Telecommand signal.

DETAILS



Gear tray detail



Stainless steel clips



Stainless steel fixing brackets for ceiling mounted or suspended versions




Connector




Sensor

PHOTOMETRY



STELLA 66 L1277W101
DC0 4000K



STELLA 66 L1277W145
DC0 4000K

TO SPECIFY:

LED waterproof luminaire IP66, for surface mounted application. Injected polycarbonate, with polyurethane gasket and polycarbonate diffuser with UV protection. Equipped with stainless steel clips and fixing brackets. Available with 2000/4000/5000/8000/10000 lm of luminous flux. Standard version with LED 4000K, CRI>80, MacAdam Step<3 and 50.000h lifetime (@L80, B10, Ta 25°C). Optional DALI dimmable LED driver, 3000K and 1h or 3h emergency unit. - as Indelague STELLA 66.

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

