



VEGA



LED

Norms: EN 60598-1, EN 60598-2-1



IP 20

IK 06

650°C

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Surface/Suspended.

Light Distribution: Direct.


Light Source: LED 4000K, CRI>90, MacAdam Step<3, 64.000h life (@L80, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.


Materials: Body: Extruded aluminium tube.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
	≤22	8	780	65	67	Ø95x200	1,2	90443.L008.E	-
	≤22	10	1100	70	64	Ø95x200	1,2	90443.L011.E	90443.L011.H
	≤25	13	1540	76	64	Ø95x200	1,2	90443.L015.E	90443.L015.H


PRISM+ - Microprismatic diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
	≤19	8	780	64	66	Ø95x200	1,2	90445.L008.E	-
	≤19	10	1100	70	64	Ø95x200	1,2	90445.L011.E	90445.L011.H
	≤19	13	1540	76	64	Ø95x200	1,2	90445.L015.E	90445.L015.H


COLOUR / FINISH

Code	Description
W	White
B	Black
G	Grey


DIMENSIONS



Recessed ceiling rose



Surface ceiling rose



Example code for order: 90443.L015.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





OPTIONS


Colour temperature



3000K

Order code
3000

Suspension kit



Recessed ceiling rose
HF
DALI

Order code


912620
912630

Surface ceiling rose
HF
DALI


912600
912610

- Transparent current supply cable included.
- To complete this option, please add ceiling rose colour.

PHOTOMETRY



**VEGA D95 LIGHT+
4000K HO**



**VEGA D95 PRISM+
4000K HO**

TO SPECIFY:

Circular LED downlight, with Ø95 mm for surface or suspended application. Available with plain opal diffuser LIGHT+ or microprismatic diffuser PRISM+ (allows a high visual comfort (UGR<19) according to EN 12464-1). Extruded aluminium body, powder coated in epoxy-polyester in white, gray and black. With three possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 64.000h lifetime (@L80, B10, Ta 25°C). Optional DALI dimmable LED driver, 3000K, suspension kit and surface or recessed ceiling rose. - as Roxo Lighting VEGA.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.





VEGA /E



LED

Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Ceiling recessed.

Light Distribution: Direct

Light Source: LED 4000K, CRI>90, MacAdam Step<3, 50.000h life (@L90, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Injected ABS.

LIGHT+ - Opal diffuser

	LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	⌀	kg	HF	DALI
		≤19	8	780	62	64	Ø100x110	Ø85	0,5	90430.L008.E	-
		≤22	10	1100	69	63	Ø100x110	Ø85	0,5	90430.L011.E	90430.L011.H
		≤22	13	1540	73	62	Ø100x110	Ø85	0,5	90430.L015.E	90430.L015.H

PRISM+ - Microprismatic diffuser

	LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	⌀	kg	HF	DALI
		≤19	8	780	63	65	Ø100x110	Ø85	0,5	90441.L008.E	-
		≤19	10	1100	70	64	Ø100x110	Ø85	0,5	90441.L011.E	90441.L011.H
		≤19	13	1540	76	64	Ø100x110	Ø85	0,5	90441.L015.E	90441.L015.H

COLOUR / FINISH

Code	Description
W	White
B	Black
G	Grey

DETAILS



Downlight detail

Example code for order: 90430.L008.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





OPTIONS

Colour temperature



3000K

Order code
3000


Safety cable




Steel safety cable

Order code
955010

PHOTOMETRY




**VEGA/E D100 LIGHT+
4000K HO**



**VEGA/E D100 PRISM+
4000K HO**

DIMENSIONS



TO SPECIFY:

Circular LED recessed downlight, with 100mm diameter and IP20/54. Available with plain opal diffuser LIGHT+ or microprismatic diffuser PRISM+ (allows a high visual comfort (UGR<19) according to EN 12464-1). Injected ABS reflector, available in white, gray or black. With 3 possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 50.000h lifetime (@L90, B10, Ta 25°C). Optional DALI dimmable LED driver and 3000K. For ceiling thicknesses of 1 to 25mm. - as Roxo Lighting VEGA /E.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.





VEGA IP



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Surface.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>90, MacAdam Step<3, 64.000h life (@L80, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium tube.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
	≤22	8	780	65	67	Ø95x206	1,2	90447.L008.E	-
	≤22	10	1100	70	64	Ø95x206	1,2	90447.L011.E	90447.L011.H
	≤25	13	1540	76	64	Ø95x206	1,2	90447.L015.E	90447.L015.H

COLOUR / FINISH

Code	Description
W	White
B	Black
G	Grey

DIMENSIONS



OPTIONS

Colour temperature



3000K

Order code
3000


Example code for order: 90447.L015.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.





PHOTOMETRY



**VEGA IP D95 LIGHT+
4000K HO**

TO SPECIFY:

Circular LED downlight, with Ø95mm and IP54 for surface application. Extruded aluminium body, powder coated in epoxy-polyester in white, gray and black. With three possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 64.000h lifetime (@L80, B10, Ta 25°C). Optional DALI dimmable LED driver and 3000K. - as Roxo Lighting VEGA IP.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.





VEGA Sq



LED

Norms: EN 60598-1, EN 60598-2-1



IP 20

IK 06

650°C

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Surface/Suspended.

Light Distribution: Direct

Light Source: LED 4000K, CRI>90, MacAdam Step<3, 64.000h life (@L80, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser



LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	HF	DALI
	≤22	8	780	70	72	100x100x200	1,3	90444.L008.E	-
	≤22	10	1100	77	70	100x100x200	1,3	90444.L011.E	90444.L011.H
	≤25	13	1540	83	70	100x100x200	1,3	90444.L015.E	90444.L015.H

PRISM+ - Microprismatic diffuser






LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	HF	DALI
	≤19	8	780	70	72	100x100x200	1,3	90446.L008.E	-
	≤19	10	1100	77	70	100x100x200	1,3	90446.L011.E	90446.L011.H
	≤19	13	1540	82	69	100x100x200	1,3	90446.L015.E	90446.L015.H

COLOUR / FINISH

Code	Description
W	White
B	Black
G	Grey

DIMENSIONS



Example code for order: 90444.L015.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





OPTIONS

Colour temperature



3000K

Order code
3000

Suspension kit



Recessed ceiling rose

HF

DALI

Order code

912720

912730

Surface ceiling rose

HF


DALI

912700


912710

- Transparent current supply cable included.
- To complete this option, please add ceiling rose colour.

PHOTOMETRY



**VEGA Sq Q100 LIGHT+
4000K HO**



**VEGA Sq Q100 PRISM+
4000K HO**

TO SPECIFY:

Square LED downlight, with 100x100 mm for surface or suspended application. Available with plain opal polycarbonate diffuser LIGHT+ or microprismatic diffuser PRISM+ (allows a high visual comfort (UGR<19) according to EN 12464-1). Extruded aluminium body, powder coated in epoxy-polyester in white, gray and black. With three possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 64.000h lifetime (@L80, B10, Ta 25°C). Optional DALI dimmable LED driver, 3000K, suspension kit and surface or recessed ceiling rose. - as Roxo Lighting VEGA Sq.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.





VEGA Sq /E



Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>90, MacAdam Step<3, 50.000h life (@L90, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Injected ABS.

LIGHT+ - Opal diffuser



LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)		kg	HF	DALI
	≤19	8	780	65	67	100x100x110	85x85	0,5	90437.L008.E	-
	≤19	10	1100	73	66	100x100x110	85x85	0,5	90437.L011.E	90437.L011.H
	≤22	13	1540	77	65	100x100x110	85x85	0,5	90437.L015.E	90437.L015.H

PRISM+ - Microprismatic diffuser



LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)		kg	HF	DALI
	≤19	8	780	67	69	100x100x110	85x85	0,5	90442.L008.E	-
	≤19	10	1100	75	68	100x100x110	85x85	0,5	90442.L011.E	90442.L011.H
	≤19	13	1540	81	68	100x100x110	85x85	0,5	90442.L015.E	90442.L015.H

COLOUR / FINISH

Code	Description
W	White
B	Black
G	Grey

DETAILS



Downlight detail

Example code for order: 90437.L008.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





OPTIONS

Colour temperature



3000K

Order code
3000


Safety cable




Steel safety cable

Order code
955010

PHOTOMETRY




**VEGA Sq /E Q100
LIGHT+ 4000K HO**



**VEGA Sq /E Q100
PRISM+ 4000K HO**

DIMENSIONS



TO SPECIFY:

Square LED recessed downlight, with 100x100mm and IP20/54. Available with plain opal diffuser LIGHT+ or microprismatic diffuser PRISM+ (allows a high visual comfort (UGR<19) according to EN 12464-1). Injected ABS reflector, available in white, gray or black. With 3 possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 50.000h lifetime (@L90, B10, Ta 25°C). Optional DALI dimmable LED driver and 3000K. For ceiling thicknesses of 1 to 25mm. - as Roxo Lighting VEGA Sq /E.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

