



VEGA Sq /E



Norms: EN 60598-1, EN 60598-2-2



230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Ceiling recessed.

Light Distribution: Direct.

Light Source: LED 4000K, CRI>90, MacAdam Step<3, 50.000h life (@L90, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Injected ABS.

LIGHT+ - Opal diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)	⚡	kg	HF	DALI
	≤19	8	780	65	67	100x100x110	85x85	0,5	90437.L008.E	-
	≤19	10	1100	73	66	100x100x110	85x85	0,5	90437.L011.E	90437.L011.H
	≤22	13	1540	77	65	100x100x110	85x85	0,5	90437.L015.E	90437.L015.H

PRISM+ - Microprismatic diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	⚡	kg	HF	DALI
	≤19	8	780	67	69	100x100x110	85x85	0,5	90442.L008.E	-
	≤19	10	1100	75	68	100x100x110	85x85	0,5	90442.L011.E	90442.L011.H
	≤19	13	1540	81	68	100x100x110	85x85	0,5	90442.L015.E	90442.L015.H

COLOUR / FINISH

Code	Description
□ W	White
■ B	Black
■ G	Grey

DETAILS



Downlight detail

Example code for order: 90437.L008.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.





OPTIONS

Colour temperature



3000K

Order code
3000


Safety cable




Steel safety cable

Order code
955010

PHOTOMETRY




**VEGA Sq /E Q100
LIGHT+ 4000K HO**



**VEGA Sq /E Q100
PRISM+ 4000K HO**

DIMENSIONS



TO SPECIFY:

Square LED recessed downlight, with 100x100mm and IP20/54. Available with plain opal diffuser LIGHT+ or microprismatic diffuser PRISM+ (allows a high visual comfort (UGR<19) according to EN 12464-1). Injected ABS reflector, available in white, gray or black. With 3 possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 50.000h lifetime (@L90, B10, Ta 25°C). Optional DALI dimmable LED driver and 3000K. For ceiling thicknesses of 1 to 25mm. - as Roxo Lighting VEGA Sq /E.

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

